





ULTRAGUARD

FEATURES & BENEFITS

- LITEGUARD 
- MIGHTYGUARD 
- ULTRAGUARD** 
- XTREMEGUARD 

POLYURETHANE

High-quality material provides strength and durability equating to extremely high load-bearing capabilities and resistance to chemical substances.

HINGE PIN

Reinforced fiberglass rod provides durability & strength to lid hinge, which will never corrode, rust or break.

LIGHTWEIGHT CONSTRUCTION WITH BUILT-IN HANDLES

Reduced shipping costs and less fatigue with handling.

FLUSH HINGES

Less failure from continued use



OPERATING TEMPERATURE

Safely withstands extreme conditions ranging from -40°F to 120°F.



MAINTENANCE

No painting or maintenance required; holds up in all weather conditions.



SAFETY WARNINGS

Symbols molded into lid.



ELASGLOW TECHNOLOGY AVAILABLE

Glow-in-the-dark strips illuminate low light environments.

1.375" CHANNEL SIZE

UNIQUE PUSH BUTTON LID FASTENERS

Lids stay shut to protect your cables.



SMOOTH HAMMER INTERLOCK DESIGN

Strong connections and easy installation.



SAFETY COLOR SCHEME

Eye-catching colors ensure safety.



SURFACE PATTERN

Tread pattern designed for stability to minimize trips and falls.



NON-SLIP SURFACE DESIGN

Safer use for pedestrian traffic at facilities, public events or job sites.



COMPLIANT

Compliant with safety regulations including NEC, OSHA, REACH & RoHS.